

FEATURES

MDV50, MDV55

- ◆ Microprocessor Based.
- ◆ LCD display.
- ◆ Selectable Speed.
- ◆ Temperature Monitoring.
- ◆ Optional Accessory - Low Viscosity Adaptor (0 Spindle).

Applications:

It is widely used to determine solvent-based adhesives, latex, Bio Chemicals, Paints, Coatings, Cosmetics, Inks, Pulp, food, etc.



HSN : 90278910

SPECIFICATIONS

PRODUCT NAME	DIGITAL VISCOMETER	
MODEL	MDV50	MDV55
Measuring range	50 mPas to 1,00,000 mPas	50 mPas to 20,00,000 mPas
No of speed	4	8
Speed Option	6,12,30,60 rpm	0.3, 0.6,1.5,3,6,12,30,60 rpm
Measuring Accuracy	±2% (Newtonian liquid)	
No of Spindle (rotor)	4 Spindle, (Optional 0 Spindle, or 1 ~50 mPas)	
Ambient Temperature	10°C to 50°C	
Interface	RS232C	
Display	LCD	
Single Measurement Auto Stop	Afer measurement result is stable, spindle stop automatically	
Power Supply	DC Adaptor, Using AC 220V/50Hz	
Packing Dimension (LxWxH)	410 × 335 × 370 mm	
Net / Gross weight	4.6 kg / 7.5kg	

* Specifications are subject to change without Notice

Monotech Lab Instruments and Calibration

B-9, Shabnam Building, MEK Industrial Estate, Opp. Fire Brigade, Mumbra, Dist. Thane 400612 Maharashtra